

Key Features & Benefits:

- Rugged Die Cast Aluminum Housing:
 - Dark bronze polyester powder coat finish
- Optical Grade Polycarbonate Lens:
 - UV stabilized
 - Molded prismatic for optimal uniformity
 - Impact resistant
- Built-in 120V Photocell
- Continuous Gasket for Weather-Tight Seal
- LEDs Mounted to and Protected by Aluminum Housing with Easy Driver Access Hinged Door
- (3) 3/4" Threaded knockouts:
 - (1) On back
 - (1) On either side
- Suitable for Wet Locations
- 10 Year Limited Warranty
- Mounting Options:
 - Direct to electrical box
 - Flush wall mount

Project: _____ Date: _____


Catalog #: _____

Notes: _____




Technical Specifications:

- Power: 17 Watts
- Lumen Output: Up to 1,700 Lumens
- Efficacy (lm/W): Up to 100 Lumens per Watt
- Kelvin: 4000K, 5000K
- CRI: >80
- Input Voltage: 120-277 VAC
- Life Span: 50,000 Hours
- Operating Temperature: -40°F - 104°F
- Dimensions (LxWxD): 5.48" x 8.38" x 3.52"



BOTTOM



FRONT

ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	KELVIN	DLC QPL CODE
ESL-WP-17W-140	17W	1,684	96	4000K	PZ434HH7
ESL-WP-17W-150	17W	1,700	100	5000K	AM78DDM

Ordering Guide:

ESL	-	WP	-	17W	-	2	-	
ESL		TYPE		WATTS		GENERATION		KELVIN*
		WP (Wall Pack)		17W		2 (2nd Generation)		40 (4000 Kelvin) 50 (5000 Kelvin)

* Other kelvin options available upon request