

Key Features & Benefits:

- Housing:
 - 5VA UV protected fiberglass housing
 - Silicone perimeter gasket
 - Stainless steel mounting brackets
- Lens:
 - Clear 100% impact modified acrylic
 - UV stabilized lens
 - Clear polycarbonate clips
- Gear Tray:
 - Pre-painted cold rolled steel
 - Easy access for quick installation
 - Secured with stainless steel wire
- Long Life:
 - 10 year warranty (12 hour run times)
 - 7 year warranty (24 hour run times)
- Ingress IP66 - Suitable for wet locations
- Control Options:
 - Photocell
 - Occupancy
- Emergency capable
- 1/2" NPT / M20 fittings on both sides



Project: _____ Date: _____

Catalog #: _____

Notes: _____



Electrical Data:


Light Specifications:

Lumen Output: Up to 2,808 Lumens
 Efficacy (lm/W): Up to 108 Lumens per Watt
 Kelvin: 3000K, 3500K, 4000K, 5000K
 Color Rendering Index (CRI): >82
 Rated Life: > 80,000 hrs


Driver Data:

Input Voltage: 120-277 VAC
 Input Power: 26W
 Input Current @ 120V: 0.217 Amps
 Input Current @ 240V: 0.108 Amps
 Input Current @ 277V: 0.094 Amps
 Total Harmonic Distortion (THD): <10%
 Power Factor: >0.99
 Operating Temperature: -4 ~ 122°F

Double Ti
Normal Distribution



Double Ti
Wide Distribution



* Made in the USA option available upon request

Catalog Data:

| | ITEM# | WATTS | LUMEN OUTPUT | EFFICACY (lm/W) | KELVIN |
|-------------------------------|-----------------------|-------|--------------|-----------------|--------|
| NARROW DISTRIBUTION | ESL-TI-VP2N-S-26W-F30 | 26W | 2,652 | 102 | 3000K |
| | ESL-TI-VP2N-S-26W-F35 | 26W | 2,652 | 102 | 3500K |
| | ESL-TI-VP2N-S-26W-F40 | 26W | 2,730 | 105 | 4000K |
| | ESL-TI-VP2N-S-26W-F50 | 26W | 2,808 | 108 | 5000K |
| WIDE DISTRIBUTION | ESL-TI-VP2W-S-26W-F30 | 26W | 2,652 | 102 | 3000K |
| | ESL-TI-VP2W-S-26W-F35 | 26W | 2,652 | 102 | 3500K |
| | ESL-TI-VP2W-S-26W-F40 | 26W | 2,730 | 105 | 4000K |
| | ESL-TI-VP2W-S-26W-F50 | 26W | 2,808 | 108 | 5000K |

Ordering Guide: Example Part Number: **ESL-TI-VP2W-S-26W-F40**



Additional Options:

- **Emergency:**
 - ESL-EMG-FDC-9.5W (Emergency Backup, 1100 Lumens, 90 Min)
- **Cord Sets:**
 - ESL-CS3W-6 (Cord Set, White, 3 wire, 6 foot)
 - ESL-CS3W-6P (Cord Set, White, 3 wire, 6 foot, Standard Plug)
 - ESL-CS3W-6TL (Cord Set, White, 3 wire, 6 foot, Twist lock Plug)
 - ESL-CS3W-12 (Cord Set, White, 3 wire, 12 foot)
 - ESL-CS3W-12P (Cord Set, White, 3 wire, 12 foot, Standard Plug)
 - ESL-CS3W-12TL (Cord Set, White, 3 wire, 12 foot, Twist lock Plug)
- **Latches:**
 - ESL-VPSS (Stainless Steel Latches)
- **Miscellaneous:**
 - ESL-SPD-277-1 (Surge Protector; 100-277V)
 - ESL-480V-SD01 (480 Volt Step Down Transformer)
- **Sensors & Controls:**
 - ESL-4OCC (Microwave Occupancy Sensor)
 - ESL-4OCP (Photocell & Microwave Occupancy Sensor)
 - ESL-4OPH (Photocell)
 - ESL-3OCC (IP65 High Bay 0-10v Dimming Sensor)
 - ESL-REM100 (Remote for EL-3OCC)
 - ESL-REM101 (Remote for ESL-4OCC, 4OCP, 4OPH)
- **Mounting:**
 - ESL-VP-CM-VP4X (Direct Mount to the Ceiling for the 2',4',8' Narrow and Wide Body Fixture - 2 per)
 - ESL-VP-45DM-VP4X (45 Degree Mount for the 2',4',8' Narrow and Wide Body Fixture - 2 per)

*Other lengths and black cord available upon request

Dimensions:

