

Key Features & Benefits:

- Rugged Die Cast Aluminum Housing:
 - Dark bronze polyester powder coat finish
- Optical Grade Polycarbonate Lens:
 - UV stabilized
 - Molded prismatic for optimal uniformity
 - Impact resistant
- Built-in 120V Photocell
- Continuous Gasket for Weather-Tight Seal
- LEDs Mounted to and Protected by Aluminum Housing with Easy Driver Access Hinged Door
- (3) 3/4" Threaded knockouts:
 - (1) On back
 - (1) On either side
- Suitable for Wet Locations
- 10 Year Limited Warranty
- Mounting Options:
 - Direct to electrical box
 - Flush wall mount

Project: _____ Date: _____


Catalog #: _____

Notes: _____




Technical Specifications:

Power: 25 Watts
 Lumen Output: Up to 2,600 Lumens
 Efficacy (lm/W): Up to 104 Lumens per Watt
 Kelvin: 4000K, 5000K
 CRI: >80
 Input Voltage: 120-277 VAC
 Life Span: 50,000 Hours
 Operating Temperature: -40°F - 104°F
 Dimensions (LxWxD): 5.48" x 8.38" x 3.52"



BOTTOM



FRONT

ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	KELVIN	DLC QPL CODE
ESL-WP-25W-240	25W	2,506	100	4000K	PLNVPULCU67W
ESL-WP-25W-250	25W	2,600	104	5000K	PLNRN7Y88MPE

Ordering Guide:

ESL	-	WP	-	25W	-	2	-	
ESL		TYPE		WATTS		GENERATION		KELVIN*
		WP (Wall Pack)		25W		2 (2nd Generation)		40 (4000 Kelvin) 50 (5000 Kelvin)

* Other kelvin options available upon request