

### Key Features & Benefits:

- Housing:
  - Strip fixture dimensions (48" x 4.25" x 3.75")
  - Die-formed and embossed code 22 gauge steel
  - Finish is high reflectance baked white enamel
- Gear Trey:
  - Flat heavy gauge die-formed code grade steel for all components
  - Ti mounting for 1 and 2 Ti bar locations
  - Easy Access for quick installation
- Long Life:
  - 10 year warranty (12 hour run times)
  - 7 year warranty (24 hour run times)
- 0-10v Dimming Available in Specific Models
- Control Options:
  - Photocell
  - Occupancy
- Emergency Capable
- 3/4" Knockouts on Both Ends



Project: \_\_\_\_\_

Date: \_\_\_\_\_

Catalog #: \_\_\_\_\_

Notes: \_\_\_\_\_



### Electrical Data:

#### Light Specifications:

Lumen Output: Up to 4,746 Lumens  
 Efficacy (lm/W): Up to 139 Lumens per Watt  
 Kelvin: 3000K, 3500K, 4000K, 5000K  
 Color Rendering Index (CRI): >82  
 Rated Life: > 80,000 hrs

#### Driver Data:

Input Voltage: 120-277 VAC  
 Input Power: 36W  
 Input Current @ 120V: 0.3 Amps  
 Input Current @ 240V: 0.15 Amps  
 Input Current @ 277V: 0.13 Amps  
 Total Harmonic Distortion (THD): <10%  
 Power Factor: >0.99  
 Operating Temperature: -4 ~ 122°F

### Catalog Data:

ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	KELVIN
ESL-Ti-WBS4-S-36W-F30	36W	4,635	136	3000K
ESL-Ti-WBS4-S-36W-F35	36W	4,648	136	3500K
ESL-Ti-WBS4-S-36W-F40	36W	4,689	138	4000K
ESL-Ti-WBS4-S-36W-F50	36W	4,746	139	5000K

\* Made in the USA option available upon request

### Ordering Guide:



<b>ESL</b>	-	<b>Ti</b>	-	<b>WBS4</b>	-	<b>S</b>	-	<b>36W</b>	-	<b>F</b>	-		-	
ESL		TYPE		SERIES		LISTING		WATTS		LENS		KELVIN		OPTIONS
		Ti Series		WBS4		S		26W (26 Watts) 30W (30 Watts) 36W (36 Watts) 44W (44 Watts)		F (Frosted)		30 (3000 Kelvin) 35 (3500 Kelvin) 40 (4000 Kelvin) 50 (5000 Kelvin)		

Example Part Number: ESL-Ti-WBS4-S-36W-F30

### Options (Add as Suffix):

- **Emergency:**
    - EMG-FDC-9.5W (Emergency Back-up, 1,100 lumens, 90 min)
  - **Sensors:**
    - ESL-1OCC (External Occupancy Sensor)
    - ESL-4OCC (Microwave Occupancy Sensor)
    - ESL-4OPH (Photocell)
    - ESL-4OCP (Photocell & Microwave Occupancy Sensor)
  - **Cord Sets:\***
    - ESL-CS3W-6 (Cord Set, White, 3 wire, 6 foot)
    - ESL-CS3W-6P (Cord Set, White, 3 wire, 6 foot, Standard Plug)
    - ESL-CS3W-12 (Cord Set, White, 3 wire, 12 foot)
    - ESL-CS3W-12P (Cord Set, White, 3 wire, 12 foot, Standard Plug)
  - **Wire Guards:**
    - ESL-WBS-WG01 (Wire Guard Body Strip Fixture)
  - **Whips: Flexible Conduit:**
    - ESL-WP3-6 (Whip, 3 wire, 6 foot)
    - ESL-WP3-12 (Whip, 3 wire, 12 foot)
  - **Mounting:**
    - ESL-VH01 (V-Hangers sets)
    - ESL-JC01 (Jack Chain - per foot)
    - ESL-HB-PM01 (Pendant Mounting)
  - **Miscellaneous:**
    - ESL-SPD-277-1 (Surge Protector; 100-277V)
    - ESL-480V-SD01 (480 Volt Step Down Transformer)
- \*Other lengths and black cord available upon request

### Dimensions:



### 2' - STRIP SERIES



NARROW SINGLE LAMP BODY	SERIES	PART NUMBER	WATTS	(lm/W)*	LUMEN OUTPUT*
	TI NBS2	ESL-Ti-NBS2-S-10W-FXX	10	133	1,330
	TI NBS2	ESL-Ti-NBS2-S-13W-FXX	13	133	1,729
— WIDE — SINGLE LAMP BODY	SERIES	PART NUMBER	WATTS	(lm/W)*	LUMEN OUTPUT*
	TI WBS2	ESL-Ti-WBS2-S-10W-FXX	10	133	1,330
	TI WBS2	ESL-Ti-WBS2-S-13W-FXX	13	133	1,729
— WIDE — TWO LAMP BODY	SERIES	PART NUMBER	WATTS	(lm/W)*	LUMEN OUTPUT*
	TI WBS2	ESL-Ti-WBS2-S-20W-FXX	20	133	2,660
	TI WBS2	ESL-Ti-WBS2-S-26W-FXX	26	133	3,458

### 4' - STRIP SERIES



NARROW SINGLE LAMP BODY	SERIES	PART NUMBER	WATTS	(lm/W)*	LUMEN OUTPUT*
	TI NBS4	ESL-Ti-NBS4-S-13W-FXX	13	133	1,729
	TI NBS4	ESL-Ti-NBS4-S-15W-FXX	15	133	1,995
	TI NBS4	ESL-Ti-NBS4-S-18W-FXX	18	133	2,394
	TI NBS4	ESL-Ti-NBS4-S-22W-FXX	22	133	2,926
	TIHO NBS4	ESL-TiHO-NBS4-S-30W-FYY	30	126	3,780
— WIDE — SINGLE LAMP BODY	SERIES	PART NUMBER	WATTS	(lm/W)*	LUMEN OUTPUT*
	TI WBS4	ESL-Ti-WBS4-S-13W-FXX	13	146	1,899
	TI WBS4	ESL-Ti-WBS4-S-15W-FXX	15	143	2,145
	TI WBS4	ESL-Ti-WBS4-S-18W-FXX	18	143	2,574
	TI WBS4	ESL-Ti-WBS4-S-22W-FXX	22	138	2,926
	TIHO WBS4	ESL-TiHO-WBS4-S-30W-FYY	30	144	4,320
— WIDE — TWO LAMP BODY	SERIES	PART NUMBER	WATTS	(lm/W)*	LUMEN OUTPUT*
	TI WBS4	ESL-Ti-WBS4-S-26W-FXX	26	144	3,558
	TI WBS4	ESL-Ti-WBS4-S-30W-FXX	30	139	3,990
	TI WBS4	ESL-Ti-WBS4-S-36W-FXX	36	139	4,768
	TI WBS4	ESL-Ti-WBS4-S-44W-FXX	44	134	5,732
	TIHO WBS4	ESL-TiHO-WBS4-S-60W-FYY	60	140	8,520

### 8' - STRIP SERIES



— WIDE — TWO LAMP BODY	SERIES	PART NUMBER	WATTS	(lm/W)*	LUMEN OUTPUT*
	TI WBS8	ESL-Ti-WBS8-S-26W-FXX	26	146	3,558
	TI WBS8	ESL-Ti-WBS8-S-30W-FXX	30	143	4,090
	TI WBS8	ESL-Ti-WBS8-S-36W-FXX	36	143	4,978
	TI WBS8	ESL-Ti-WBS8-S-44W-FXX	44	140	5,942
	TIHO WBS8	ESL-TiHO-WBS8-S-60W-FYY	60	144	8,520
— WIDE — TWO LAMP BODY	SERIES	PART NUMBER	WATTS	(lm/W)*	LUMEN OUTPUT*
	TI WBS8	ESL-Ti-WBS8-S-52W-FXX	52	144	6,896
	TI WBS8	ESL-Ti-WBS8-S-60W-FXX	60	139	8,590
	TI WBS8	ESL-Ti-WBS8-S-72W-FXX	72	139	9,976
	TI WBS8	ESL-Ti-WBS8-S-88W-FXX	88	134	11,694
	TIHO WBS8	ESL-TiHO-WBS8-S-120W-FYY	120	140	17,120

\* At 5000K. See spec sheets for other kelvins  
XX = 30, 35, 40, or 50 for kelvin temperature  
YY = 40 or 50 for kelvin temperature