

Key Features & Benefits:

- Glass Free
- Vibration and Impact Resistant
- Optical Grade Polycarbonate Lens Tubes:
 - UV protected
 - Fire retardant
 - Corrosion resistant
- Damp Rated
- Zero Maintenance
- Superior Heat Management
- Die-formed Heavy Gauge Steel

Project: _____ Date: _____

Catalog #: _____

Notes: _____



Electrical Data:

Light Specifications:

Lumen Output: Up to 3,450 Lumens
 Efficacy (lm/W): Up to 115 Lumens per Watt
 Kelvin: 3500K, 4000K, 5000K
 Color Rendering Index (CRI): >82
 Rated Life: >50,000 Hours
 Dimensions (LxWxH): 48.25" x 4.37" x 4.37"

Driver Data:

Input Voltage: 120-277 VAC
 Input Power: 30W
 Input Current @ 120V: 0.25 Amps
 Input Current @ 240V: 0.125 Amps
 Input Current @ 277V: 0.108 Amps
 Total Harmonic Distortion (THD): <10%
 Power Factor: >0.99
 Operating Temperature: -4 ~ 122°F

Catalog Data:

ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	KELVIN
ESL-ID-F313-S-30W-F35	30W	3,330	111	3500K
ESL-ID-F313-S-30W-F40	30W	3,390	113	4000K
ESL-ID-F313-S-30W-F50	30W	3,450	115	5000K

Ordering Guide:

ESL	-	ID	-	F313	-	S	-	30W	-	F	-	
ESL		TYPE		SERIES		CLASS		WATTS		LENS		KELVIN
		ID Series		F313		S		30W (30 Watts)		F (Frosted)		35 (3500 Kelvin) 40 (4000 Kelvin) 50 (5000 Kelvin)
												OPTIONS

Example Part Number: ESL-ID-F313-S-30W-F35

Options (Add as Suffix):

- **Sensors:**
 - ESL-4OCC (Occupancy Sensor, On/Off, 8'-20' Mounting)

Dimensions:

