

Key Features & Benefits:

- Glass-Free, Vibration and Impact Resistant
- Optical Grade Polycarbonate Lens Tubes:
 - UV protected
 - Fire retardant
 - Corrosion resistant
- Zero Maintenance
- Superior Heat Management
- Die-Formed Heavy Gauge Steel
- Long Life:
 - 10 year warranty (12 hour run times)
 - 7 year warranty (24 hour run times)
- Safe - No Glass to Shatter
- Optional 0-10v Dimmable

Project: _____

Date: _____

Catalog #: _____

Notes: _____



Light Specifications:

Lumen Output: Up to 5,331 Lumens
 Efficacy (lm/W): Up to 122 Lumens per Watt
 Kelvin: 3,000K, 3500K, 4000K, 5000K
 Color Rendering Index (CRI): >82
 Rated Life: >80,000 Hours

Driver Data:

Input Voltage: 120-277 VAC
 Input Power: 44W
 Input Current @ 120V: 0.364 Amps
 Input Current @ 240V: 0.182 Amps
 Input Current @ 277V: 0.158 Amps
 THD: <10%
 Power Factor: >0.99
 Operating Temperature: -4 ~ 122°F

Catalog Data:

ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	KELVIN	DLC QPL CODE
ESL-Ti-F414-S-44W-F30	44W	4,620	105	3000K	P2DVK6RM
ESL-Ti-F414-S-44W-F35	44W	4,708	107	3500K	PH2I6QFN
ESL-Ti-F414-S-44W-F40	44W	4,796	109	4000K	POEKIBML
ESL-Ti-F414-S-44W-F50	44W	4,972	113	5000K	PXDAFUCU

Ordering Guide:

ESL	Ti	F414	S	44W	F	
ESL	TYPE	SERIES	LISTING	WATTS	LENS	KELVIN
	Ti Series	F414	S	26W (26 Watts) 30W (30 Watts) 36W (36 Watts) 44W (44 Watts)	F (Frosted)	30 (3000 Kelvin) 35 (3500 Kelvin) 40 (4000 Kelvin) 50 (5000 Kelvin)

Example Part Number: ESL-Ti-F414-S-44W-F30

Dimensions:

