

Key Features & Benefits:

- Extremely Quick Installation:
 - No rewiring necessary
 - No tombstones
 - Does not require access into ceiling plenum or extra junction boxes for installation
 - Quick Connect technology
- Available Kits:
 - 3 Ti Retrofit Plate for parabolic and lensed troffers
 - 2 Ti Retrofit Plate for lensed troffers
- 36 Total Available Configurations
 - 2,780 to 9,391 lumens
 - 3000K, 3500K, 4000K, and 5000K available in Ti Series
 - 4000K and 5000K available in TiHO Series
- Material
 - Single piece design with pre-drilled holes allowing quick and easy installation
 - Die-formed and embossed code 22 gauge steel
 - High reflectance, baked white enamel finish
- Long Life
 - 10 year warranty (12 hour run times)
 - 7 year warranty (24 hour run times)
- Control Options
 - Photocell
 - Occupancy
- Emergency Capable



Project: _____ Date: _____

Catalog #: _____

Notes: _____



Technical Data:

Light Specifications:

Lumen Output: Up to 6,720 Lumens
 Efficacy (lm/W): Up to 112 Lumens per Watt
 Kelvin: 4000K, 5000K
 Color Rendering Index (CRI): >82
 Rated Life: > 80,000 hrs

Driver Data:

Input Voltage: 120-277 VAC
 Driver Output: Dual Output
 Output Power: 60 Watts
 Input Current @ 120V: 0.5 Amps
 Input Current @ 240V: 0.25 Amps
 Input Current @ 277V: 0.217 Amps
 Total Harmonic Distortion (THD): <10%
 Operating Temperature: -4 ~ 122°F

Catalog Data:

ITEM#	WATTS	TOTAL KIT LUMENS	EFFICACY (lm/W)	KELVIN
ESL-TiHO-PK24-S-60W-3L-F40	60W	6,600	110	4000K
ESL-TiHO-PK24-S-60W-3L-F50	60W	6,720	112	5000K

Ordering Guide:

ESL	-	TiHO	-	PK24	-	S	-	60W	-	2L	-	F	-		-	
ESL		TYPE		SERIES		CLASS		WATTS		Ti		LENS		KELVIN		OPTIONS
		TiHO Series		PK24 (2'x4' Plate Kit)		S		60W (60 Watts)		2L (Two Ti)		F (Frosted)		40 (4000 Kelvin) 50 (5000 Kelvin)		

Alternate 2'x4' Ti Plate Kit Options:



3L Output


Options (Add as Suffix):

- ESL-EMG-FDC-30W (Emergency Back Up, DC, 30 Watt)
- ESL-4OCC (Occupancy Sensor, 0-10v Dimming, 20' Max. Mounting)
- ESL-REM-101 (Hand Held Remote to Program ESL-2OCC, ESL-4OCC, ESL-5OCC)


What's Included:

- (1) Retrofit Plate
- (2) LED Ti Bar
- (1) LED Driver
- (4) Ti Mounting Clips
- (4) Self Tapping Screws
- (1) UL1598C Certification Label

Dimensions:



Side View



Front View