

Key Features & Benefits:

- Glass-Free, Vibration and Impact Resistant
- Optical Grade Polycarbonate Lens Tubes:
 - UV protected
 - Fire retardant
 - Corrosion resistant
- Ideal for Stairwells
- Zero Maintenance
- Die-Formed Heavy Gauge Steel
- Safe - No Glass to Shatter

Project: _____

Date: _____

Catalog #: _____

Notes: _____



Light Specifications:

Lumen Output: Up to 1,950 Lumens
 Efficacy (lm/W): Up to 130 Lumens per Watt
 Kelvin: 3000K, 3500K, 4000K, 5000K
 Color Rendering Index (CRI): >82
 Rated Life: >80,000 Hours

Driver Data:

Input Voltage: 120-277 VAC
 Input Power: 15W
 Input Current @ 120V: 0.128 Amps
 Input Current @ 240V: 0.064 Amps
 Input Current @ 277V: 0.055 Amps
 THD: <10%
 Power Factor: >0.99
 Operating Temperature: -4 ~ 122°F

Catalog Data:

ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	KELVIN
ESL-ID-F304-S-15W-F30	15W	1,830	122	3000K
ESL-ID-F304-S-15W-F35	15W	1,860	124	3500K
ESL-ID-F304-S-15W-F40	15W	1,890	126	4000K
ESL-ID-F304-S-15W-F50	15W	1,950	130	5000K

Ordering Guide:

ESL	-	ID	-	F304	-	S	-	15W	-	F	-		-	
ESL		TYPE		SERIES		CLASS		WATTS		LENS		KELVIN		OPTIONS
		ID Series		F304		S		15W (15 Watts)		F (Frosted)		30 (3000 Kelvin) 35 (3500 Kelvin) 40 (4000 Kelvin) 50 (5000 Kelvin)		

Example Part Number: ESL-ID-F304-S-15W-F30

Options (Add as Suffix):

ESL-4OCC-LDD	Photocell/Occupancy Sensor for Standard Mounting, Dip Switch, 0-10v
ESL-REM-100	Hand Held Remote to Program 2OCC-HDD, 3OCC, 4OCC-LDD and 8OCC
ESL-CS3W-6P	Cord Set, White, 3 wire, 6 foot, Standard Plug
ESL-CS3W-6TL	Cord Set, White, 3 wire, 6 foot, Twist lock Plug
ESL-CS3W-12P	Cord Set, White, 3 wire, 12 foot, Standard Plug
ESL-CS3W-12TL	Cord Set, White, 3 wire, 12 foot, Twist lock Plug
ESL-WP3-6	Whip, 3 wire, 6 foot
ESL-WP3-12	Whip, 3 wire, 12 foot
ESL-WBS-HH01	Hooker Hanger Mount
ESL-WBS-PM01	Pendant Mounting
ESL-SPD-277-1	Surge Protector; (100-277 VAC)
ESL-480V-SD01	Hard Sire Surge Protector; (100-277 VAC) Max Discharge Current: 20kA

Dimensions:

