

### Key Features & Benefits:

- Glass-Free, Vibration and Impact Resistant
- Optical Grade Polycarbonate Lens Tubes:
  - UV protected
  - Fire retardant
  - Corrosion resistant
- Ideal for Stairwells
- Zero Maintenance
- Die-Formed Heavy Gauge Steel
- Long Life:
  - 10 year warranty (12 hour run times)
  - 7 year warranty (24 hour run times)
- Safe - No Glass to Shatter
- Tamper Resistant Occupancy Sensor
- Emergency Options for Egress Requirements

Project: \_\_\_\_\_

Date: \_\_\_\_\_

Catalog #: \_\_\_\_\_

Notes: \_\_\_\_\_



### Light Specifications:

Lumen Output: Up to 3,840 Lumens  
 Efficacy (lm/W): Up to 128 Lumens per Watt  
 Kelvin: 3000K, 3500K, 4000K, 5000K  
 Color Rendering Index (CRI): >82  
 Rated Life: >80,000 Hours

### Driver Data:

Input Voltage: 120-277 VAC  
 Input Power: 30W  
 Dimming: 0-10v  
 Input Current @ 120V: 0.250 Amps  
 Input Current @ 240V: 0.125 Amps  
 Input Current @ 277V: 0.108 Amps  
 THD: <10%  
 Power Factor: >0.99  
 Operating Temperature: -4 ~ 122°F

### Catalog Data:

ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	KELVIN	DLC QPL CODE
ESL-Ti-F314-S-30W-F30	30W	3,570	119	3000K	P5BKIZBG
ESL-Ti-F314-S-30W-F35	30W	3,630	121	3500K	PFDJQACF
ESL-Ti-F314-S-30W-F40	30W	3,690	123	4000K	PWYWE30S
ESL-Ti-F314-S-30W-F50	30W	3,840	128	5000K	PJP2UOY7

### Ordering Guide:

<b>ESL</b>	-	<b>Ti</b>	-	<b>F314</b>	-	<b>S</b>	-	<b>30W</b>	-	<b>F</b>	-		-	
ESL		TYPE		SERIES		CLASS		WATTS		LENS		KELVIN		OPTIONS
		Ti Series		F314		S		26W (26 Watts) 30W (30 Watts) 36W (36 Watts) 44W (44 Watts)		F (Frosted)		30 (3000 Kelvin) 35 (3500 Kelvin) 40 (4000 Kelvin) 50 (5000 Kelvin)		

Example Part Number: ESL-Ti-F314-S-30W-F30

### Options (Add as Suffix):

- ESL-EMG-FDC-30W      Emergency Back Up, DC, 30 Watt
- ESL-EMG-2DC-9W      Emergency Back Up, DC, 9 Watt, External Battery
- ESL-4OCC-LDD      Photocell/Occupancy Sensor for Standard Mounting, Dip Switch, 0-10v
- ESL-REM-100      Hand Held Remote to Program 2OCC-HDD, 3OCC, 4OCC-LDD and 8OCC

### Dimensions:

