

Key Features & Benefits:

- Glass-Free, Vibration and Impact Resistant
- Optical Grade Polycarbonate Lens Tubes:
 - UV protected
 - Fire retardant
 - Corrosion resistant
- Ideal for Stairwells
- Zero Maintenance
- Die-Formed Heavy Gauge Steel
- Long Life:
 - 10 year warranty (12 hour run times)
 - 7 year warranty (24 hour run times)
- Safe - No Glass to Shatter
- Tamper Resistant Occupancy Sensor
- Emergency Options for Egress Requirements

Project: _____

Date: _____

Catalog #: _____

Notes: _____



Light Specifications:

Lumen Output: Up to 6,780 Lumens
 Efficacy (lm/W): Up to 113 Lumens per Watt
 Kelvin: 4000K, 5000K
 Color Rendering Index (CRI): >82
 Rated Life: >80,000 Hours

Driver Data:

Input Voltage: 120-277 VAC
 Input Power: 60W
 Dimming: 0-10v
 Input Current @ 120V: 0.5 Amps
 Input Current @ 240V: 0.25 Amps
 Input Current @ 277V: 0.217 Amps
 THD: <10%
 Power Factor: >0.99
 Operating Temperature: -4 ~ 122°F

Catalog Data:

ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	KELVIN	DLC QPL CODE
ESL-TiHO-F314-S-60W-F40	60W	6,540	109	4000K	PG7DG6ZM
ESL-TiHO-F314-S-60W-F50	60W	6,780	113	5000K	PLVCOBQ0

Ordering Guide:

ESL	-	TiHO	-	F314	-	S	-	60W	-	F	-		-	
ESL		TYPE		SERIES		CLASS		WATTS		LENS		KELVIN		OPTIONS
		TiHO Series		F314		S		60W (60 Watts)		F (Frosted)		40 (4000 Kelvin) 50 (5000 Kelvin)		

Example Part Number: ESL-TiHO-F314-S-60W-F40

Options (Add as Suffix):

- ESL-EMG-FDC-30W Emergency Back Up, DC, 30 Watt
- ESL-EMG-2DC-9W Emergency Back Up, DC, 9 Watt, External Battery
- ESL-4OCC-LDD Photocell/Occupancy Sensor for Standard Mounting, Dip Switch, 0-10v
- ESL-REM-100 Hand Held Remote to Program 2OCC-HDD, 3OCC, 4OCC-LDD and 8OCC

Dimensions:

